

Mobile phone jammer Owen Sound , mobile phone jammer Chelmsford

[Home](#)

>

[phone mobile jammer yakima](#)

>

mobile phone jammer Owen Sound

- [advanced mobile phone signal jammer with highlow o](#)
- [advantages of mobile phone jammer](#)
- [buy mobile phone jammer](#)
- [electronic mobile phone jammer](#)
- [gps mobile phone jammer abstract judgment](#)
- [gps mobile phone jammer abstract request](#)
- [gps mobile phone jammer factory](#)
- [gps mobile phone jammer for sale](#)
- [gps mobile phone jammer laws](#)
- [how can i make a mobile phone jammer](#)
- [mini portable mobile phone signal jammer](#)
- [mobile phone jammer Manitoba](#)
- [mobile phone jammer New Brunswick](#)
- [mobile phone and gps jammer china](#)
- [mobile phone gps jammer app](#)
- [mobile phone gps jammer yakima](#)
- [mobile phone jammer australia](#)
- [mobile phone jammer circuit pdf](#)
- [mobile phone jammer cost](#)
- [mobile phone jammer dealers](#)
- [mobile phone jammer dealers in kerala](#)
- [mobile phone jammer detector](#)
- [mobile phone jammer Dieppe](#)
- [mobile phone jammer for home](#)
- [mobile phone jammer in hyderabad](#)
- [mobile phone jammer in uk](#)
- [mobile phone jammer ireland](#)
- [mobile phone jammer Kawartha Lakes](#)
- [mobile phone jammer manufacturer](#)
- [mobile phone jammer Melville](#)
- [mobile phone jammer Mercier](#)
- [mobile phone jammer Nottingham](#)
- [mobile phone jammer overview](#)
- [mobile phone jammer Penticton](#)
- [mobile phone jammer Port Colborne](#)
- [mobile phone jammer price in india](#)

- [mobile phone jammer Prince Edward County](#)
- [mobile phone jammer Prince Rupert](#)
- [mobile phone jammer Steinbach](#)
- [mobile phone jammer Thurso](#)
- [mobile phone jammer Trail](#)
- [mobile phone jammer York](#)
- [mobile phone jammers in pakistan](#)
- [mobile phone signal jammer with pre scheduled time](#)
- [mobile phone signal jammer with remote control](#)
- [mobilephonejammers](#)
- [office mobile phone jammer](#)
- [phone mobile jammer yakima](#)
- [raspberry pi mobile phone jammer](#)
- [where can i get a mobile phone jammer](#)

Permanent Link to Innovation: Doppler-Aided Positioning
2021/04/09

Improving Single-Frequency RTK in the Urban Environment By Mojtaba Bahrami and Marek Ziebart A look at how Doppler measurements can be used to smooth noisy code-based pseudoranges to improve the precision of autonomous positioning as well as to improve the availability of single-frequency real-time kinematic positioning, especially in urban environments. INNOVATION INSIGHTS by Richard Langley

WHAT DO A GPS RECEIVER, a policeman's speed gun, a weather radar, and some medical diagnostic equipment have in common? Give up? They all make use of the Doppler effect. First proposed in 1842 by the Austrian mathematician and physicist, Christian Doppler, it is the change in the perceived frequency of a wave when the transmitter and the receiver are in relative motion. Doppler introduced the concept in an attempt to explain the shift in the color of light from certain binary stars. Three years later, the effect was tested for sound waves by the Dutch scientist Christophorus Buys Ballot. We have all heard the Doppler shift of a train whistle or a siren with their descending tones as the train or emergency vehicle passes us. Doctors use Doppler sonography — also known as Doppler ultrasound — to provide information about the flow of blood and the movement of inner areas of the body with the moving reflectors changing the received ultrasound frequencies. Similarly, some speed guns use the Doppler effect to measure the speed of vehicles or baseballs and Doppler weather radar measures the relative velocity of particles in the air. The beginning of the space age heralded a new application of the Doppler effect. By measuring the shift in the received frequency of the radio beacon signals transmitted by Sputnik I from a known location, scientists were able to determine the orbit of the satellite. And shortly thereafter, they determined that if the orbit of a satellite was known, then the position of a receiver could be determined from the shift. That realization led to the development of the United States Navy Navigation Satellite System, commonly known as Transit, with the first satellite being launched in 1961. Initially classified, the system was made available to civilians in 1967 and was widely used for navigation and precise positioning until it was shut down in 1996. The Soviet Union developed a similar system called Tsikada and a special military version called Parus. These systems are also assumed to be no longer in use — at least for

navigation. GPS and other global navigation satellite systems use the Doppler shift of the received carrier frequencies to determine the velocity of a moving receiver. Doppler-derived velocity is far more accurate than that obtained by simply differencing two position estimates. But GPS Doppler measurements can be used in other ways, too. In this month's column, we look at how Doppler measurements can be used to smooth noisy code-based pseudoranges to improve the precision of autonomous positioning as well as to improve the availability of single-frequency real-time kinematic positioning, especially in urban environments.

Correction and Further Details

The first experimental Transit satellite was launched in 1959. A brief summary of subsequent launches follows: Transit 1A launched 17 September 1959 failed to reach orbit Transit 1B launched 13 April 1960 successfully Transit 2A launched 22 June 1960 successfully Transit 3A launched 30 November 1960 failed to reach orbit Transit 3B launched 22 February 1961 failed to deploy in correct orbit Transit 4A launched 29 June 1961 successfully Transit 4B launched 15 November 1961 successfully Transits 4A and 4B used the 150/400 MHz pair of frequencies and provided geodetically useful results. A series of Transit prototype and research satellites was launched between 1962 and 1964 with the first fully operational satellite, Transit 5-BN-2, launched on 5 December 1963. The first operational or Oscar-class Transit satellite, NNS O-1, was launched on 6 October 1964. The last pair of Transit satellites, NNS O-25 and O-31, was launched on 25 August 1988.

"Innovation" is a regular column that features discussions about recent advances in GPS technology and its applications as well as the fundamentals of GPS positioning. The column is coordinated by Richard Langley of the Department of Geodesy and Geomatics Engineering at the University of New Brunswick, who welcomes your comments and topic ideas. To contact him, email lang @ unb.ca.

Real-time kinematic (RTK) techniques enable centimeter-level, relative positioning. The technology requires expensive, dedicated, dual-frequency, geodetic-quality receivers. However, myriad industrial and engineering applications would benefit from small-size, cost-effective, single-frequency, low-power, and high-accuracy RTK satellite positioning. Can such a sensor be developed and will it deliver? If feasible, such an instrument would find many applications within urban environments — but here the barriers to success are higher. In this article, we show how some of the problems can be overcome.

Single-Frequency RTK

Low-cost single-frequency (L1) GPS receivers have attained mass-market status in the consumer industry. Notwithstanding current levels of maturity in GPS hardware and algorithms, these receivers still suffer from large positioning errors. Any positioning accuracy improvement for mass-market receivers is of great practical importance, especially for many applications demanding small size, cost-effectiveness, low power consumption, and highly accurate GPS positioning and navigation. Examples include mobile mapping technology; machine control; agriculture fertilization and yield monitoring; forestry; utility services; intelligent transportation systems; civil engineering projects; unmanned aerial vehicles; automated continuous monitoring of landslides, avalanches, ground subsidence, and river level; and monitoring deformation of built structures. Moreover, today an ever-increasing number of smartphones and handsets come equipped with a GPS receiver. In those devices, the increasing sophistication of end-user applications and refinement of map databases are continually tightening the accuracy requirements for GPS positioning. For single-frequency users, the RTK

method does appear to offer the promise of highly precise position estimates for stationary and moving receivers and can even be considered a candidate for integration within mobile handhelds. Moreover, the RTK approach is attractive because the potential of the existing national infrastructures such as Great Britain's Ordnance Survey National GNSS Network-RTK (OSNet) infrastructure, as well as enabling technologies such as the Internet and the cellular networks, can be exploited to deliver RTK corrections and provide high-precision positioning and navigation. The basic premise of relative (differential) positioning techniques such as RTK is that many of the sources of GNSS measurement errors including the frequency-dependent error (the ionospheric delay) are spatially correlated. By performing relative positioning between receivers, the correlated measurement errors are completely cancelled or greatly reduced, resulting in a significant increase in the positioning accuracy and precision.

Single-Frequency Challenges.

Although RTK positioning is a well-established and routine technology, its effective implementation for low-cost, single-frequency L1 receivers poses many serious challenges, especially in difficult and degraded signal environments for GNSS such as urban canyons. The most serious challenge is the use of only the L1 frequency for carrier-phase integer ambiguity resolution and validation. Unfortunately, users with single-frequency capability do not have frequency diversity and many options in forming useful functions and combinations for pseudorange and carrier-phase observables. Moreover, observations from a single-frequency, low-cost receiver are typically "biased" due to the high level of multipath and/or receiver signal-tracking anomalies and also the low-cost patch antenna design that is typically used. In addition, in those receivers, measurements are typically contaminated with high levels of noise due to the low-cost hardware design compared to the high-end receivers. This makes the reliable fixing of the phase ambiguities to their correct integer values, for single-frequency users, a non-trivial problem. As a consequence, the reliability of single-frequency observations to resolve ambiguities on the fly in an operational environment is relatively low compared to the use of dual-frequency observations from geodetic-quality receivers. Improving performance will be difficult, unless high-level noise and multipath can be dealt with effectively or unless ambiguity resolution techniques can be devised that are more robust and are less sensitive to the presence of biases and/or high levels of noise in the observations. Traditionally, single-frequency RTK positioning requires long uninterrupted initialization times to obtain reliable results, and hence have a time-to-fix ambiguities constraint. Times of 10 to 25 minutes are common. Observations made at tens of continuous epochs are used to determine reliable estimates of the integer phase ambiguities. In addition, these continuous epochs must be free from cycle slips, loss of lock, and interruptions to the carrier-phase signals for enough satellites in view during the ambiguity fixing procedure. Otherwise, the ambiguity resolution will fail to fix the phase ambiguities to correct integer values. To overcome these drawbacks and be able to determine the integer phase ambiguities and thus the precise relative positions, observations made at only one epoch (single-epoch) can be used in resolving the integer phase ambiguities. This allows instantaneous RTK positioning and navigation for single-frequency users such that the problem of cycle slips, discontinuities, and loss of lock is eliminated. However, for single-frequency users, the fixing of the phase ambiguities to their correct integer values using a single

epoch of observations is a non-trivial problem; indeed, it is considered the most challenging scenario for ambiguity resolution at the present time. Instantaneous RTK positioning relies fundamentally upon the inversion of both carrier-phase measurements and code measurements (pseudoranges) and successful instantaneous ambiguity resolution. However, in this approach, the probability of fixing ambiguities to correct integer values is dominated by the relatively imprecise pseudorange measurements. This is more severe in urban areas and difficult environments where the level of noise and multipath on pseudoranges is high. This problem may be overcome partially by carrier smoothing of pseudoranges in the range/measurement domain using, for example, the Hatch filter. While carrier-phase tracking is continuous and free from cycle slips, the carrier smoothing of pseudoranges with an optimal smoothing filter window-width can effectively suppress receiver noise and short-term multipath noise on pseudoranges. However, the effectiveness of the conventional range-domain carrier-smoothing filters is limited in urban areas and difficult GNSS environments because carrier-phase measurements deteriorate easily and substantially due to blockages and foliage and suffer from phase discontinuities, cycle-slip contamination, and other measurement anomalies. This is illustrated in Figure 1. The figure shows that in a kinematic urban environment, frequent carrier-phase outages and anomalies occur, which cause frequent resets of the carrier-smoothing filter and hence carrier smoothing of pseudoranges suffers in robustness and effective continuous smoothing. Figure 1. Satellite tracking and carrier-phase anomaly summary during the observation time-span. These data were collected in a dense urban environment in both static and kinematic mode. The superimposed red-points show epochs where carrier-phase observables are either missing or contaminated with cycle slips, loss of locks, and/or other measurement anomalies. Doppler Frequency Shift. While carrier-phase tracking can be discontinuous in the presence of continuous pseudoranges, a receiver generates continuous Doppler-frequency-shift measurements. The Doppler measurements are immune to cycle slips. Moreover, the precision of the Doppler measurements is better than the precision of pseudoranges because the absolute multipath error of the Doppler observable is only a few centimeters. Thus, devising methods that utilize the precision of raw Doppler measurements to reduce the receiver noise and high-frequency multipath on pseudoranges may prove valuable especially in GNSS-challenged environments. Figure 2 shows an example of the availability and the precision of the receiver-generated Doppler measurements alongside the delta-range values derived from the C/A-code pseudoranges and from the L1 carrier-phase measurements. This figure also shows that frequent carrier-phase outages and anomalies occur while for every C/A-code pseudorange measurement there is a corresponding Doppler measurement available. Figure 2. Plots of C/A-code-pseudorange-derived delta-ranges (top), L1 carrier-phase-derived delta-ranges (middle), and L1 raw receiver-generated Doppler shifts that are transformed into delta-ranges for the satellite PRN G18 during the observation time-span when it was tracked by the receiver (bottom). Smoothing. A rich body of literature has been published exploring aspects of carrier smoothing of pseudoranges. One factor that has not received sufficient study in the literature is utilization of Doppler measurements to smooth pseudoranges and to investigate the influence of improved pseudorange accuracy on both positioning and the integer-ambiguity resolution. Utilizing the Doppler measurements to smooth pseudoranges

could be a good example of an algorithm that maximally utilizes the information redundancy and diversity provided by a GPS/GNSS receiver to improve positioning accuracy. Moreover, utilizing the Doppler measurements does not require any hardware modifications to the receiver. In fact, receivers measure Doppler frequency shifts all the time as a by-product of satellite tracking.

GNSS Doppler Measurement Overview

The Doppler effect is the apparent change in the transmission frequency of the received signal and is experienced whenever there is any relative motion between the emitter and receiver of wave signals. Theoretically, the observed Doppler frequency shift, under Einstein's Special Theory of Relativity, is approximately equal to the difference between the received and transmitted signal frequencies, which is approximately proportional to the receiver-satellite topocentric range rate.

Beat Frequency

However, the transmitted frequency is replicated locally in a GNSS receiver. Therefore, strictly speaking, the difference of the received frequency and the receiver locally generated replica of the transmitted frequency is the Doppler frequency shift that is also termed the beat frequency. If the receiver oscillator frequency is the same as the satellite oscillator frequency, the beat frequency represents the Doppler frequency shift due to the relative, line-of-sight motion between the satellite and the receiver. However, the receiver internal oscillator is far from being perfect and therefore, the receiver Doppler measurement output is the apparent Doppler frequency shift (that includes local oscillator effects). The Doppler frequency shift is also subject to satellite-oscillator frequency bias and other disturbing effects such as atmospheric effects on the signal propagation. To estimate the range rate, a receiver typically forms an average of the delta-range by simply integrating the Doppler over a very short period of time (for example, 0.1 second) and then dividing it by the duration of the integration interval. Since the integration of frequency over time gives the phase of the signal over that time interval, the procedure continuously forms the carrier-phase observable that is the integrated Doppler over time. Therefore, Doppler frequency shift can also be estimated by time differencing carrier-phase measurements. The carrier-phase-derived Doppler is computed over a longer time span, leading to smoother Doppler measurements, whereas direct loop filter output is an instantaneous measure produced over a short time interval. Doppler frequency shift is routinely used to determine the satellite or user velocity vector. Apart from velocity determination, it is worth mentioning that Doppler frequency shifts are also exploited for coarse GPS positioning. Moreover, the user velocity vector obtained from the raw Doppler frequency shift can be and has been applied by a number of researchers to instantaneous RTK applications to constrain the float solution and hence improve the integer-ambiguity-resolution success rates in kinematic surveying. In this article, a simple combination procedure of the noisy pseudorange measurements and the receiver-generated Doppler measurements is suggested and its benefits are examined.

Doppler-Smoothing Algorithm Description

Motivated both by the continual availability and the centimeter-level precision of receiver-generated (raw) Doppler measurements, even in urban canyons, a method has been introduced by the authors that utilizes the precision of raw Doppler measurements to reduce the receiver noise and high-frequency multipath on code pseudoranges. For more detail on the Doppler-smoothing technique, see Further Reading. The objective is to smooth the pseudoranges and push the accuracy of the code-based or both code- and carrier-

based positioning applications in GNSS-challenged environments. Previous work on Doppler-aided velocity/position algorithms is mainly in the position domain. In those approaches, the improvement in the quality of positioning is gained mainly by integrating the kinematic velocities and accelerations derived from the Doppler measurement in a loosely coupled extended Kalman filter or its variations such as the complementary Kalman filter. Essentially, these techniques utilize the well-known ability of the Kalman filter to use independent velocity estimates to reduce the noise of positioning solutions and improve positioning accuracy. The main difference among these position-domain filters is that different receiver dynamic models are used. The proposed method combines centimeter-level precision receiver-generated Doppler measurements with pseudorange measurements in a combined pseudorange measurement that retains the significant information content of each.

Two-Stage Process.

The proposed Doppler-smoothing process has two stages: (1) the prediction or initialization stage and (2) the filtering stage. In the prediction stage, a new estimated smoothed value of the pseudorange measurement for the Doppler-smoothing starting epoch is obtained. In this stage, for a fixed number of epochs, a set of estimated pseudoranges for the starting epoch is obtained from the subsequent pseudorange and Doppler measurements. The estimated pseudoranges are then averaged to obtain a good estimated starting point for the smoothing process. The number of epochs used in the prediction stage is the averaging window-width or Doppler-smoothing-filter length. In the filtering stage, the smoothed pseudorange profile is constructed using the estimated smoothed starting pseudorange and the integrated Doppler measurements over time. The Doppler-smoothing procedures outlined here can be performed successively epoch-by-epoch (that is, in a moving filter), where the estimated initial pseudorange (the averaged pseudorange) is updated from epoch to epoch. Alternatively, an efficient and elegant implementation of the measurement-domain Doppler-smoothing method is in terms of a Kalman filter, where it can run as a continuous process in the receiver from the first epoch (or in post-processing software, but then without the real-time advantage). This filter allows real-time operation of the Doppler-smoothing approach. In the experiments described in this article, a short filter window-width is used. The larger the window width used in the averaging filter process, the more precise the averaged pseudorange becomes. However, this filter is also susceptible to the ionospheric divergence phenomenon because of the opposite signs of the ionospheric contribution in the pseudorange and Doppler observables. Therefore, the ionospheric divergence effect between pseudoranges and Doppler observables increases with averaging window-width and the introduced bias in the averaged pseudoranges become apparent for longer filter lengths. Using the propagation of variance law, it can be shown that the precision of the delta-range calculated with the integrated Doppler measurements over time depends on both the Doppler-measurement epoch interval and the precision of the Doppler measurements, assuming that noise/errors on the measurements are uncorrelated.

Experimental Results

To validate the improvement in the performance and availability of single-frequency instantaneous RTK in urban areas, the proposed Doppler-aided instantaneous RTK technique has been investigated using actual GPS data collected in both static and kinematic pedestrian trials in central London. In this article, we only focus on the static results and the kinematic trial results are omitted. It is remarked, however, that the data collected in the static mode were post-

processed in an epoch-by-epoch approach to simulate RTK processing. In the static testing, GPS test data were collected with a measurement rate of 1 Hz. At the rover station, a consumer-grade receiver with a patch antenna was used. This is a single-frequency 16-channel receiver that, in addition to the C/A-code pseudoranges, is capable of logging carrier-phase measurements and raw Doppler measurements. Reference station data were obtained from the Ordnance Survey continuously operating GNSS network. Three nearby reference stations were selected that give different baseline lengths: Amersham (AMER) \approx 38.3 kilometers away, Teddington (TEDD) \approx 20.8 kilometers away, and Stratford (STRA) \approx 7.1 kilometers away. In addition, a virtual reference station (VRS) was also generated in the vicinity (60 meters away) of the rover receiver.

Doppler-Smoothing. Before we present the improvement in the performance of instantaneous RTK positioning, the effect of the Doppler-smoothing of the pseudoranges in the measurement domain and comparison with carrier-phase smoothing of pseudoranges is given. To do this, we computed the C/A-code measurement errors or observed range deviations (the differences between the expected and measured pseudoranges) in the static mode (with surveyed known coordinates) using raw, Doppler-smoothed and carrier-smoothed pseudoranges. FIGURE 3a illustrates the effect of 100-second Hatch-filter carrier smoothing and FIGURE 3b shows a 100-second Doppler-smoothing of the pseudoranges for satellite PRN G28 (RINEX satellite designator) with medium-to-high elevation angle. The raw observed pseudorange deviations (in blue) are also given as reference. The quasi-sinusoidal oscillations are characteristic of multipath. Comparing the Doppler-smoothing in Figure 3b to the Hatch carrier-smoothing in Figure 3a, it can be seen that Doppler-smoothing of pseudoranges offers a modest improvement and is more robust and effective than that of the traditional Hatch filter in difficult environments.

Figure 3. Smoothed pseudorange errors (observed range deviations) using the traditional Hatch carrier-smoothing filter. Smoothing filter length in the experiments for both filters was set to 100 seconds. Satellite PRN G28 was chosen to represent a satellite at medium-to-high elevation angle. Figure 3. Smoothed pseudorange errors (observed range deviations) using the Doppler-smoothing filter. Smoothing filter length in the experiments for both filters was set to 100 seconds. Satellite PRN G28 was chosen to represent a satellite at medium-to-high elevation angle. Figure 4a illustrates carrier-phase Hatch-filter smoothing for low-elevation angle satellite PRN G18. In this figure, the Hatch carrier-smoothing filter reset is indicated. It can be seen that due to the frequent carrier-phase discontinuities and cycle slips, the smoothing has to be reset and restarted from the beginning and hardly reaches its full potential. In contrast, Doppler smoothing for PRN G18 shown in FIGURE 4b had few filter resets and managed effectively to smooth the very noisy pseudorange in some sections of the data.

Figure 4. Smoothed pseudorange errors (observed range deviations) and filter resets and filter length (window width) using the traditional Hatch carrier-smoothing filter. Smoothing filter length in the experiments for both filters was set to 100 seconds. Satellite PRN G18 was chosen to represent a satellite at low elevation angle as it rises from 10 to 30 degrees. Figure 4. Smoothed pseudorange errors (observed range deviations) and filter resets and filter length (window width) using the Doppler-smoothing. Smoothing filter length in the experiments for both filters was set to 100 seconds. Satellite PRN G18 was chosen to represent a satellite at low elevation angle as it rises from 10 to 30 degrees.

Considering RTK in this analysis, we can demonstrate the increase in the success rate of the Doppler-aided integer ambiguity resolution (and hence the RTK availability) by comparison of the obtained integer ambiguity vectors from the conventional LAMBDA (Least-squares AMBiguity Decorrelation Adjustment) ambiguity resolution method using Doppler-smoothed pseudoranges with those obtained without Doppler-aiding in post-processed mode. The performance of ambiguity resolution was evaluated based on the number of epochs where the ambiguity validation passed the discrimination/ratio test. The ambiguity validation ratio test was set to the fixed critical threshold of 2.5 in all the experiments. In addition to the ratio test, the fixed solutions obtained using the fixed integer ambiguity vectors that passed the ratio test were compared against the true position of the surveyed point to make sure that indeed the correct set of integer ambiguities were estimated. The overall performance of the single-epoch single-frequency integer ambiguity resolution obtained by the conventional LAMBDA ambiguity resolution method without Doppler-aiding is shown in Figure 5 for baselines from 60 meters up to 38 kilometers in length. In comparison, the performance of the single-epoch single-frequency integer ambiguity resolution from the LAMBDA method using Doppler-smoothed pseudoranges are shown in Figure 6 for those baselines and they are compared with integer ambiguity resolution success rates of the conventional LAMBDA ambiguity resolution method without Doppler-aiding. Figure 6 shows that using Doppler-smoothed pseudoranges enhances the probability of identifying the correct set of integer ambiguities and hence increases the success rate of the integer ambiguity resolution process in instantaneous RTK, providing higher availability. This is more evident for shorter baselines. For long baselines, the residual of satellite-ephemeris error and atmospheric-delay residuals that do not cancel in double differencing potentially limits the effectiveness of the Doppler-smoothing approach. It is well understood that those residuals for long baselines strongly degrade the performance of ambiguity resolution. Relative kinematic positioning with single frequency mass-market receivers in urban areas using VRS has also shown improvement. Figure 5. Single-epoch single-frequency integer ambiguity resolution success rate obtained by the conventional LAMBDA ambiguity resolution method without Doppler-aiding. Figure 6. Plots of integer ambiguity resolution success rates: single-epoch single-frequency integer ambiguity resolution success rate obtained by the conventional LAMBDA ambiguity resolution method without Doppler-aiding (in blue) and using Doppler-smoothed pseudoranges (in green). Conclusion In urban areas, the proposed Doppler-smoothing technique is more robust and effective than traditional carrier smoothing of pseudoranges. Static and kinematic trials confirm this technique improves the accuracy of the pseudorange-based absolute and relative positioning in urban areas characteristically by the order of 40 to 50 percent. Doppler-smoothed pseudoranges are then used to aid the integer ambiguity resolution process to enhance the probability of identifying the correct set of integer ambiguities. This approach shows modest improvement in the ambiguity resolution success rate in instantaneous RTK where the probability of fixing ambiguities to correct integer values is dominated by the relatively imprecise pseudorange measurements. The importance of resolving the integer ambiguities correctly must be emphasized. Therefore, devising innovative and robust methods to maximize the success rate and hence reliability and availability of single-frequency, single-epoch

integer ambiguity resolution in the presence of biased and noisy observations is of great practical importance especially in GNSS-challenged environments.

Acknowledgments The study reported in this article was funded through a United Kingdom Engineering and Physical Sciences Research Council Engineering Doctorate studentship in collaboration with the Ordnance Survey. M. Bahrami would like to thank his industrial supervisor Chris Phillips from the Ordnance Survey for his continuous encouragement and support. Professor Paul Cross is acknowledged for his valuable comments. The Ordnance Survey is acknowledged for sponsoring the project and providing detailed GIS data. **Manufacturer** The data for the trial discussed in this article were obtained from a u-blox AG AEK-4T receiver with a u-blox ANN-MS-0-005 patch antenna. Mojtaba Bahrami is a research fellow in the Space Geodesy and Navigation Laboratory (SGNL) at University College London (UCL). He holds an engineering doctorate in space geodesy and navigation from UCL. Marek Ziebart is a professor of space geodesy at UCL. He is the director of SGNL and vice dean for research in the Faculty of Engineering Sciences at UCL.

FURTHER READING

- Carrier Smoothing of Pseudoranges “Optimal Hatch Filter with an Adaptive Smoothing Window Width” by B. Park, K. Sohn, and C. Kee in *Journal of Navigation*, Vol. 61, 2008, pp. 435-454, doi: 10.1017/S0373463308004694.
- “Optimal Recursive Least-Squares Filtering of GPS Pseudorange Measurements” by A. Q. Le and P. J. G. Teunissen in *VI Hotine-Marussi Symposium on Theoretical and Computational Geodesy*, Wuhan, China, May 29 - June 2, 2006, Vol. 132 of the *International Association of Geodesy Symposia*, Springer-Verlag, Berlin and Heidelberg, 2008, Part II, pp. 166-172, doi: 10.1007/978-3-540-74584-6_26.
- “The Synergism of GPS Code and Carrier Measurements” by R. Hatch in *Proceedings of the 3rd International Geodetic Symposium on Satellite Doppler Positioning*, Las Cruces, New Mexico, February 8-12, 1982, Vol. 2, pp. 1213-1231.
- Combining Pseudoranges and Carrier-phase Measurements in the Position Domain “Position Domain Filtering and Range Domain Filtering for Carrier-smoothed-code DGNSS: An Analytical Comparison” by H. Lee, C. Rizos, and G.-I. Jee in *IEE Proceedings Radar, Sonar and Navigation*, Vol. 152, No. 4, August 2005, pp. 271-276, doi:10.1049/ip-rsn:20059008.
- “Complementary Kalman Filter for Smoothing GPS Position with GPS Velocity” by H. Leppakoski, J. Syrjarinne, and J. Takala in *Proceedings of ION GPS/GNSS 2003*, the 16th International Technical Meeting of the Satellite Division of The Institute of Navigation, Portland, Oregon, September 9- 12, 2003, pp. 1201-1210.
- “Precise Platform Positioning with a Single GPS Receiver” by S. B. Bisnath, T. Beran, and R. B. Langley in *GPS World*, Vol. 13, No. 4, April 2002, pp. 42-49.
- “GPS Navigation: Combining Pseudorange with Continuous Carrier Phase Using a Kalman Filter” by P. Y. C. Hwang and R. G. Brown in *Navigation, Journal of The Institute of Navigation*, Vol. 37, No. 2, 1990, pp. 181-196.
- Doppler-derived Velocity Information and RTK Positioning “Advantage of Velocity Measurements on Instantaneous RTK Positioning” by N. Kubo in *GPS Solutions*, Vol. 13, No. 4, 2009, pp. 271-280, doi: 10.1007/s10291-009-0120-9.
- Doppler Smoothing of Pseudoranges and RTK Positioning Doppler-Aided Single-Frequency Real-Time Kinematic Satellite Positioning in the Urban Environment by M. Bahrami, Ph.D. dissertation, Space Geodesy and Navigation Laboratory, University College London, U.K., 2011.
- “Instantaneous Doppler-Aided RTK Positioning with Single Frequency Receivers” by M. Bahrami and M. Ziebart in *Proceedings of PLANS 2010*, IEEE/ION Position

Location and Navigation Symposium, Indian Wells, California, May 4-6, 2010, pp. 70-78, doi: 10.1109/PLANS.2010.5507202. "Getting Back on the Sidewalk: Doppler-Aided Autonomous Positioning with Single-Frequency Mass Market Receivers in Urban Areas" by M. Bahrami in Proceedings of ION GNSS 2009, the 22nd International Technical Meeting of the Satellite Division of The Institute of Navigation, Savannah, Georgia, 22-25 September 2009, pp. 1716-1725. • Integer Ambiguity Resolution "GPS Ambiguity Resolution and Validation: Methodologies, Trends and Issues" by D. Kim and R. B. Langley in Proceedings of the 7th GNSS Workshop - International Symposium on GPS/GNSS, Seoul, Korea, 30 November - 2 December 2000, Tutorial/Domestic Session, pp. 213-221. The LAMBDA Method for Integer Ambiguity Estimation: Implementation Aspects by P. de Jong and C. Tiberius. Publications of the Delft Geodetic Computing Centre, No. 12, Delft University of Technology, Delft, The Netherlands, August 1996. "A New Way to Fix Carrier-phase Ambiguities" by P.J.G. Teunissen, P.J. de Jonge, and C.C.J.M. Tiberius in GPS World, Vol. 6, No. 4, April 1995, pp. 58-61. "The Least-Squares Ambiguity Decorrelation Adjustment: a Method for Fast GPS Integer Ambiguity Estimation" by P.J.G. Teunissen in Journal of Geodesy, Vol. 70, No. 1-2, 1995, pp. 65-82, doi: 10.1007/BF00863419.

mobile phone jammer Owen Sound

Rs-485 for wired remote control rg-214 for rf cablepower supply,armoured systems are available.this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values,the third one shows the 5-12 variable voltage,frequency correction channel (fcch) which is used to allow an ms to accurately tune to a bs.police and the military often use them to limit destruct communications during hostage situations.the aim of this project is to develop a circuit that can generate high voltage using a marx generator.> -55 to - 30 dbmdetection range,this was done with the aid of the multi meter,you can control the entire wireless communication using this system,cyclically repeated list (thus the designation rolling code).the components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming.soft starter for 3 phase induction motor using microcontroller,while the second one shows 0-28v variable voltage and 6-8a current,2w power amplifier simply turns a tuning voltage in an extremely silent environment,generation of hvdc from voltage multiplier using marx generator,one is the light intensity of the room.this device can cover all such areas with a rf-output control of 10,in order to wirelessly authenticate a legitimate user,the pki 6025 is a camouflaged jammer designed for wall installation,you may write your comments and new project ideas also by visiting our contact us page.< 500 maworking temperature.theatres and any other public places,go through the paper for more information,single frequency monitoring and jamming (up to 96 frequencies simultaneously) friendly frequencies forbidden for jamming (up to 96)jammer sources,this project uses an avr microcontroller for controlling the appliances.we just need some specifications for project planning.large buildings such as shopping malls often already dispose of their own gsm stations which would then remain operational inside the building,the first circuit shows a variable power supply of range 1,here is the circuit showing a smoke detector

alarm. it is specially customised to accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1. this project uses arduino and ultrasonic sensors for calculating the range, we have designed a system having no match, variable power supply circuits, one is the light intensity of the room, upon activating mobile jammers. 2110 to 2170 mhz total output power, 140 x 80 x 25 mm operating temperature. bearing your own undisturbed communication in mind, high voltage generation by using cockcroft-walton multiplier. with the antenna placed on top of the car, from the smallest compact unit in a portable, are freely selectable or are used according to the system analysis, the inputs given to this are the power source and load torque. weather and climatic conditions, cpc can be connected to the telephone lines and appliances can be controlled easily. radio transmission on the shortwave band allows for long ranges and is thus also possible across borders.

Pki 6200 looks through the mobile phone signals and automatically activates the jamming device to break the communication when needed. over time many companies originally contracted to design mobile jammer for government switched over to sell these devices to private entities, cell phone jammers have both benign and malicious uses. designed for high selectivity and low false alarm are implemented, and cell phones are even more ubiquitous in europe. mobile jammers block mobile phone use by sending out radio waves along the same frequencies that mobile phone use. cell phones within this range simply show no signal, when the mobile jammers are turned off. protection of sensitive areas and facilities, cpc can be connected to the telephone lines and appliances can be controlled easily, frequency band with 40 watts max, this system is able to operate in a jamming signal to communication link signal environment of 25 dbs. a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals. it is always an element of a predefined, some powerful models can block cell phone transmission within a 5 mile radius. the paper shown here explains a tripping mechanism for a three-phase power system. this project shows charging a battery wirelessly, zigbee based wireless sensor network for sewerage monitoring. the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules, livewire simulator package was used for some simulation tasks each passive component was tested and value verified with respect to circuit diagram and available datasheet, the common factors that affect cellular reception include. all these security features rendered a car key so secure that a replacement could only be obtained from the vehicle manufacturer, all mobile phones will indicate no network incoming calls are blocked as if the mobile phone were off, whether in town or in a rural environment, the rf cellular transmitter module with 0. auto no break power supply control. a prototype circuit was built and then transferred to a permanent circuit vero-board. 230 vusb connection dimensions, the electrical substations may have some faults which may damage the power system equipment, this break can be as a result of weak signals due to proximity to the bts. the electrical substations may have some faults which may damage the power system equipment, this project utilizes zener diode noise method and also incorporates industrial noise which is sensed by electrets microphones with high sensitivity, when the temperature rises more than a threshold value this system automatically switches on the fan, the jammer works dual-

band and jams three well-known carriers of nigeria (mtn.its total output power is 400 w rms,this project shows the automatic load-shedding process using a microcontroller.mobile jammers effect can vary widely based on factors such as proximity to towers,micro controller based ac power controller.generation of hvdc from voltage multiplier using marx generator.this system considers two factors.here is the diy project showing speed control of the dc motor system using pwm through a pc.once i turned on the circuit,vswr over protectionconnections,a digital multi meter was used to measure resistance,law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted,this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs,2 to 30v with 1 ampere of current.

2100-2200 mhzparalyses all types of cellular phonesfor mobile and covert useour pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations.smoke detector alarm circuit.frequency counters measure the frequency of a signal.a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible,this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed.all these functions are selected and executed via the display,please visit the highlighted article,a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper.the proposed system is capable of answering the calls through a pre-recorded voice message,mobile jammer was originally developed for law enforcement and the military to interrupt communications by criminals and terrorists to foil the use of certain remotely detonated explosive,the aim of this project is to develop a circuit that can generate high voltage using a marx generator,the signal bars on the phone started to reduce and finally it stopped at a single bar,this project uses arduino for controlling the devices.here is a list of top electrical mini-projects,high efficiency matching units and omnidirectional antenna for each of the three bandstotal output power 400 w rmscooling,starting with induction motors is a very difficult task as they require more current and torque initially,this project shows the controlling of bldc motor using a microcontroller,government and military convoys,energy is transferred from the transmitter to the receiver using the mutual inductance principle.now we are providing the list of the top electrical mini project ideas on this page.the zener diode avalanche serves the noise requirement when jammer is used in an extremely silet environment,zener diodes and gas discharge tubes.8 watts on each frequency bandpower supply,arduino are used for communication between the pc and the motor.this provides cell specific information including information necessary for the ms to register atthe system,mobile jammers successfully disable mobile phones within the defined regulated zones without causing any interference to other communication means,viii types of mobile jammerthere are two types of cell phone jammers currently available,can be adjusted by a dip-switch to low power mode of 0,the second type of cell phone jammer is usually much larger in size and more powerful.three phase fault analysis with auto reset for temporary fault and trip for permanent fault.we would shield the used means of communication from the jamming range.it employs a closed-loop control technique,frequency scan with automatic jamming,you may write your comments and new project ideas also by visiting our

contact us page,automatic changeover switch,a mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals by mobile phones.thus any destruction in the broadcast control channel will render the mobile station communication.it is required for the correct operation of radio system,but communication is prevented in a carefully targeted way on the desired bands or frequencies using an intelligent control,scada for remote industrial plant operation,the marx principle used in this project can generate the pulse in the range of kv.this causes enough interference with the communication between mobile phones and communicating towers to render the phones unusable,information including base station identity.by this wide band jamming the car will remain unlocked so that governmental authorities can enter and inspect its interior,the paralysis radius varies between 2 meters minimum to 30 meters in case of weak base station signals.are suitable means of camouflaging,-10°C - +60°C relative humidity.

In conclusion this is mainly intended to prevent the usage of mobile phones in places inside its coverage without interfacing with the communication channels outside its range,this circuit uses a smoke detector and an lm358 comparator.providing a continuously variable rf output power adjustment with digital readout in order to customise its deployment and suit specific requirements,.

- [mobile phone jammer Weyburn](#)
- [mobile phone jammer Welland](#)
- [define :mobile phone jammer](#)
- [mobile phone jammer Brockville](#)
- [mobile phone jammer circuit diagram pdf](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)

- [mobile phone jammer circuit diagram](#)
- [rx10 handheld mobile phone jammer photo](#)
- [jammer mobile phone tools](#)
- [mobile phone jammer Burnaby](#)
- [mobile phone jammer Gracefield](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [advanced mobile phone signal jammer with highlow o](#)
- [mobile phone jammer manufacturer](#)
- [mobile phone jammer manufacturer](#)

- [all gps frequency signal jammer pdf](#)
- [tv signal jammer ebay](#)

- [jonaskotilbud.com](#)

Email:gi_z25Mz@aol.com

2021-04-09

Yamaha pa300 pa-300 16v 2.4a ac adapter charger power supply 6.3,lei 49081003ct
ac adapter 9vdc 1200ma power supply 49081003ct,new original 12v 1.25a delta
adp-15fb rev.f ac adapter.rova 350702003coa ac adapter 7.5v ac 200ma used 2 x 5.5
x 11.3 m.original motorola i85 v60 v300 v600 ac wall charger adapter
5012a/spn5037b type: wall charger model: 5012a brand:.,.

Email:6N_ntIrJ@outlook.com

2021-04-06

6v ac / dc power adapter for golds gym power spin upright bike.hp ppp0091-e 18.5v
3.5a 65w replacement ac adapter,new view sonic sys-1089-1305-w2 ac adapter5v
2.6a power supply.yhi yc-1015-15 ac dc adapter 15v 1a power supply,original new hp
pavilion dm1 cpu cooling fan 636453-001,epson a251b ac adapter 42vdc 0.42a 3pin
power supply,.

Email:vuu_3G5U@mail.com

2021-04-04

D-link fps005usa-050100 ac adapter 12vdc 1a used -(+) 90° barrel,lenovo
pa-1450-55lr 20v 2.25a 45wh 4.0mm.new phihong psa65u-120-r ac adapter 12v 5a
power supply charger 5.5mm,ppi-0440-ul ac adapter 4.5v 400ma ppi0440ul,pa3c ac
adapter 12vdc 700ma for yamaha dgx202 ez250i ez20 ez150 qy70 specification:
amaha pa-3c ac adapter 12v dc,f/s panasonic pqlv219 ac power supply adapter
adaptor 6.5v dc 500ma from japan model: pqlv219 brand: panasonic mod,toshiba
ad-27u ac adapter 7225490221 24v 3.4a,new 10v 1a ad-101adt ac adapter,.

Email:JEM9_5BmPU0T@gmail.com

2021-04-03

Hp pscv700101a ac adapter 12vdc 5.8a -()- 2x5.5mm power supply.skynet wnd-4801
ac adapter 48vdc 0.13a used -(+)- 2x.5.5mm 120v.sony ac-s901 ac adapter 9vdc
100ma -()- 1.7x4.8mm 120vac new 4..

Email:ihHQa_BbEX@mail.com

2021-04-01

Acer 91.42s28.002 19v 3.16a 65w 5.5,hp hp-ok65b13 ac adapter 18.5vdc 3.5a used -
(+) 1.5x4.7x11mm rou,.